

NETTOYANT RESINE HOMOLO FCAM00017 - CTG220047/00/01_SGP

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : NETTOYANT RESINE HOMOLO FCAM00017
Product code : CTG220047/00/01_SGP.
UFI : 4D1C-Y86Q-P00X-FPPN

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Registered company name : CONDIVEX.
Address : Z.I de la porte rouge.27150.ETREPAGNY.FRANCE.
Telephone : 0232558064. Fax : 0232558584.
RegMI.fca@fareva.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Skin corrosion, Category 1B (Skin Corr. 1B, H314).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

The propellant gas is not taken into account when determining the health and environmental classification of the mixture.

2.2. Label elements

Detergent mixture (see section 15).

Mixture for aerosol application.

Hazard pictograms :



GHS02



GHS05

Signal Word :

DANGER

Product identifiers :

EC 215-185-5 **SODIUM HYDROXIDE**

Hazard statements :

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H314

Causes severe skin burns and eye damage.

Precautionary statements - General :

P102

Keep out of reach of children.

Precautionary statements - Prevention :

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211

Do not spray on an open flame or other ignition source.

NETTOYANT RESINE HOMOLO FCAM00017 - CTG220047/00/01_SGP

P251 Do not pierce or burn, even after use.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Storage :
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
Precautionary statements - Disposal :
P501 Eliminate the contents / container according to the local regulations.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European Chemicals Agency (ECHA) under article 59 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances >= 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	Classification (EC) 1272/2008	Note	%
INDEX: 601_004_00_0 CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32 BUTANE	GHS02, GHS04 Dgr Flam. Gas 1A, H220 Press. Gas, H280	C [i] [vii]	2.5 <= x % < 10
INDEX: 011_002_00_6 CAS: 1310-73-2 EC: 215-185-5 REACH: 01-2119457892-27 SODIUM HYDROXIDE	GHS05 Dgr Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318	[i]	2.5 <= x % < 10
INDEX: A137166 CAS: 137-16-6 EC: 205-281-5 REACH: 01-2119527780--39 SODIUM N-LAUROYLSARCOSINATE	GHS06, GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318 Acute Tox. 2, H330		0 <= x % < 1
INDEX: A110258 CAS: 110-25-8 EC: 701-177-3 REACH: 01-2119488991-20 (Z)-N-MÉTHYL-N-(1-OXO-9-OCTADECÉNYL)GLYCINE	GHS07, GHS05, GHS09 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318 Acute Tox. 4, H332 Aquatic Acute 1, H400 M Acute = 1		0 <= x % < 1

Specific concentration limits:

Identification	Specific concentration limits	ATE
INDEX: 011_002_00_6 CAS: 1310-73-2 EC: 215-185-5 REACH: 01-2119457892-27 SODIUM HYDROXIDE	Skin Corr. 1A: H314 C>= 5% Skin Corr. 1B: H314 2% <= C < 5% Skin Irrit. 2: H315 0.5% <= C < 2% Eye Dam. 1: H318 C>= 2% Eye Irrit. 2: H319 0.5% <= C < 2%	
INDEX: A137166 CAS: 137-16-6 EC: 205-281-5 REACH: 01-2119527780--39 SODIUM N-LAUROYLSARCOSINATE	Skin Irrit. 2: H315 >=30% Eye Dam. 1: H318 C>= 30% Eye Irrit. 2: H319 1% <= C < 30%	

NETTOYANT RESINE HOMOLO FCAM00017 - CTG220047/00/01_SGP

INDEX: A110258 CAS: 110-25-8 EC: 701-177-3 REACH: 01-2119488991-20 (Z)-N-MÉTHYL-N-(1-OXO-9-OCTADECÉNY L)GLYCINE		inhalation: ATE = 1.8 mg/l 4h (dust/mist)
--	--	--

Information on ingredients :

(Full text of H-phrases: see section 16)

[i] Substance for which maximum workplace exposure limits are available.

[vii] Propellant gas

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin :

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

Seek medical attention immediately, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Eliminate any possible source of ignition and ventilate the premises.

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

Use some absorbent.

The elimination must be carried out by a registered salvage professional.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention :

Handle in well-ventilated areas.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

NETTOYANT RESINE HOMOLO FCAM00017 - CTG220047/00/01_SGP

Do not breathe in aerosols.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- UK :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm 1450 mg/m3	750 ppm 1810 mg/m3		Carc	
1310-73-2		2 mg/m3			

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard ISO 16321.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard ISO 16321.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- PVC (polyvinyl chloride)

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

NETTOYANT RESINE HOMOLO FCAM00017 - CTG220047/00/01_SGP

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of spraying, wear protective clothing against chemical risks and against sprayed liquid (type 4) in accordance with EN14605/A1 to prevent skin contact.

Wear suitable protective clothing and, in particular, an apron and boots. These items of clothing shall be maintained in good condition and cleaned after use.

Suitable type of protective boots :

In the event of minor spatter, wear protective chemical-resistant boots or half-boots in accordance with standard EN13832-2 with hydrocarbon-resistant soles resistant in accordance with standard EN20346/A1.

In the event of prolonged contact, wear boots or half-boots with hydrocarbon-resistant soles in accordance with standard EN20346/A1 and liquid-chemical-resistant and waterproof uppers in accordance with standard EN13832-3.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state : Fluid liquid.
Spray.

Colour

Unspecified

Odour

Odour threshold : Not stated.

Melting point

Melting point/melting range : Not specified.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not specified.

Flammability

Flammability (solid, gas) : Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) Not stated.

:

Explosive properties, upper explosivity limit (%) Not stated.

:

Flash point

Flash point interval : Not relevant.

Auto-ignition temperature

Self-ignition temperature : Not specified.

Decomposition temperature

Decomposition point/decomposition range : Not specified.

pH

pH : 13.00 0.5.
Strongly basic.

pH (aqueous solution) : Not stated.

Kinematic viscosity

Viscosity : Not stated.

Viscosity: $\nu < 7 \text{ mm}^2/\text{s}$ (40°C)

NETTOYANT RESINE HOMOLO FCAM00017 - CTG220047/00/01_SGP

Solubility

Water solubility : Soluble.
Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density and/or relative density

Density : > 1

Relative vapour density

Vapour density : Not stated.

Particle characteristics

The mixture does not contain nanoforms.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

Aerosols

Chemical combustion heat : Not specified.
Inflammation time : Not specified.
Deflagration density : Not specified.
Inflammation distance : Not specified.
Flame height : Not specified.
Flame duration : Not specified.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat
- frost
- flames and hot surfaces
- accumulation of electrostatic charges.

10.5. Incompatible materials

Keep away from :

- strong oxidising agents
- strong acids

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

NETTOYANT RESINE HOMOLO FCAM00017 - CTG220047/00/01_SGP

- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1. Substances

a) Acute toxicity :

SODIUM N-LAUROYLSARCOSINATE (CAS: 137-16-6)

Inhalation route (Dusts/mist) : 0.25 < LC50 ≤ 0.5 mg/l
Species : Rat
OECD Guideline 403 (Acute Inhalation Toxicity)
Duration of exposure : 4 h

(Z)-N-MÉTHYL-N-(1-OXO-9-OCTADECÉNYL)GLYCINE (CAS: 110-25-8)

Oral route : LD50 > 5000 mg/kg body weight
Species : Rat
OECD Guideline 420 (Acute Oral Toxicity Fixed Dose Method)

Inhalation route (Dusts/mist) : LC50 = 1.8 mg/l
Species : Rat
OECD Guideline 403 (Acute Inhalation Toxicity)
Duration of exposure : 4 h

b) Skin corrosion/skin irritation :

No data available.

c) Serious damage to eyes/eye irritation :

No data available.

d) Respiratory or skin sensitisation :

No data available.

e) Germ cell mutagenicity :

No data available.

f) Carcinogenicity :

No data available.

g) Reproductive toxicant :

No data available.

h) Specific target organ systemic toxicity - single exposure :

No data available.

i) Specific target organ systemic toxicity - repeated exposure :

No data available.

j) Aspiration hazard :

No data available.

11.1.2. Mixture

11.1.2.1 Information on hazard classes

a) Acute toxicity :

Oral route : No data available.

Dermal route : No data available.

Inhalation route (Dusts/mist) : No data available.

NETTOYANT RESINE HOMOLO FCAM00017 - CTG220047/00/01_SGP

b) Skin corrosion/skin irritation :

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure between three minutes and one hour.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

c) Serious damage to eyes/eye irritation :

No data available.

d) Respiratory or skin sensitisation :

No data available.

e) Germ cell mutagenicity :

No data available.

f) Carcinogenicity :

No data available.

g) Reproductive toxicant :

No data available.

h) Specific target organ systemic toxicity - single exposure :

No data available.

i) Specific target organ systemic toxicity - repeated exposure :

No data available.

j) Aspiration hazard :

No data available.

11.1.2.2 Other information

11.2. Information on other hazards

Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with effects on human health.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

(Z)-N-MÉTHYL-N-(1-OXO-9-OCTADECÉNYL)GLYCINE (CAS: 110-25-8)

Fish toxicity :

LC50 < 10 mg/l

Species : *Leuciscus idus*

Duration of exposure : 96 h

REACH Method C.1 (Acute Toxicity for Fish)

Crustacean toxicity :

EC50 = 0.43 mg/l

Factor M = 1

Species : *Daphnia magna*

Duration of exposure : 48 h

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity :

ECr50 = 6.3 mg/l

Species : *Desmodesmus subspicatus*

Duration of exposure : 72 h

REACH Method C.3 (Algal Inhibition test)

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

(Z)-N-MÉTHYL-N-(1-OXO-9-OCTADECÉNYL)GLYCINE (CAS: 110-25-8)

NETTOYANT RESINE HOMOLO FCAM00017 - CTG220047/00/01_SGP

Biodegradability :

Rapidly degradable.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with environmental effects.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2022 [41-22] - ICAO/IATA 2024 [65]).

14.1. UN number or ID number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable, corrosive

14.3. Transport hazard class(es)

- Classification :



2.1+8

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5FC	-	2.1+8	-	1 L	190 327 344 625	E0	1	D

NETTOYANT RESINE HOMOLO FCAM00017 - CTG220047/00/01_SGP

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	2	See SP63	-	See SP277	F-D. S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	2.1	8	-	Forbidden	Forbidden	Forbidden	Forbidden	-	-
	2.1	8	-	Forbidden	Forbidden	-	-	-	-

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2023/707.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2024/2564. (ATP 22)

Container information:

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

Particular provisions :

No data available.

Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):
<https://echa.europa.eu/substances-restricted-under-reach>.

Authorisations agreed under Title VII of Regulation (EC) No.1907/2006 (REACH):

The mixture does not contain any substance subject to authorisation according to Annex XIV of REACH Regulation (EC) No 1907/2006: <https://echa.europa.eu/fr/authorisation-list>.

Substances that deplete the ozone layer (EC Regulation No. 1005/2009, Montreal Protocol) :

The mixture does not contain any substance posing a risk to the ozone layer.

Persistent organic pollutants (POP) (Regulation (EU) 2019/1021):

The mixture does not contain a persistent organic pollutant.

PIC Regulation (EU) No 649/2012 concerning the export and import of hazardous chemicals (Rotterdam Convention):

The mixture is not subject to the Prior Informed Consent (PIC) procedure.

Explosives precursors :

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

Labelling for detergents (EC Regulation No. 648/2004,907/2006) :

- less than 5 % : anionic surfactants
- 5 % or over but less than 15 % : aliphatic hydrocarbons

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

GHS02 : Flame

GHS05 : Corrosion

IATA : International Air Transport Association.

IMDG : International Maritime Dangerous Goods.

ICAO : International Civil Aviation Organisation

PBT: Persistent, bioaccumulable and toxic.

PIC: Prior Informed Consent.

POP: Persistent Organic Pollutant.

RID : Regulations concerning the International carriage of Dangerous goods by rail.

SVHC : Substances of very high concern.

vPvB : Very persistent, very bioaccumulable.

WGK : Wassergefährdungsklasse (Water Hazard Class).